




**DMX Decoder 107**

FCCT-042DMX-107

Decoder 107 DMX512 Decoder **Benefits:**

- **Compatible with DMX512 Standard**
- **Auto ID address** / No Manual DIP Switch Setting
- Suitable for most RGB Flexible LED strips and fixture, between DC12V to DC24V, include RGB RibbonStrips, RGB Water Lights, RGB Flexistrip, RGB Superflux, RGB Tube Light and RGB SMD LED Bar.
- High Output / 2A per channel
- Up to 170units of Decoder under the same DMX512 Control



**Specification Features**

**Physical Dimensions**

<b>Dimensions</b>	L65mm x W37mm x H21mm
<b>Control method</b>	Controlled by standard DMX
<b>Housing</b>	ABS
<b>Operating Temperature</b>	-20°C to 50°C (-68°F to 122°F)
<b>Starting Temperature</b>	-10°C to 50°C (-50°F to 122°F)
<b>IP Rating</b>	IP40
<b>Sub-control</b>	None
<b>Accessory</b>	None
<b>Weight</b>	120g

**Electrical**

<b>Power Input</b>	DC 12V~24V	<b>Control Mechanism</b>	DMX Control Device
<b>Current</b>	2A max. per channel	<b>Data Wiring</b>	IP65 Connector / Wires