



Power Low Bay Light 30W Benefits:

- Luxtre Series / **Extreme High Light Output** / Best at **3 Meter Height**
- Extremely Low Operation Cost / Energy Efficient (30W VS 120W)
- **ONE LED Module** / Natural Illumination
- Closest to Gas Tube Lighting / **No Ghost Effect**
- **Fixture Acts as Heat Sink** / LED is only **10°C** more than Surface
- Super Long Life / Zero Maintenance
- Simple Design / Solid Construct / Parts Easily Replaceable
- **Constant Current Design**
- Environmentally Friendly / No Toxic / Reduce Waste
- CO2 Reduction (based on 50,K Hour): **2871KG** =
- Mercury Reduction (compared to fluorescent): **41.67mg**
- Application: Hallway, Supermarket, Dinning Area, Stairway, etc.

Power Low Bay Light 30W


FHB01-W01HP-UA30 (White, 120°)
FHB01-WW01HP-UA30 (Warm White, 120°)



Specification Features

Color Range	White, Warm White
Dimensions	Φ340mm x H200mm
Light Source	30W High Power LED
Housing	Die-casting aluminum
Operating Temperature	-40°C to 50°C (-40°F to 122°F)
Starting Temperature	-40°C to 50°C (-40°F to 122°F)
IP Rating	IP40
LED source life	50, 000 hours
Design	Sling mounted
Accessory	None
Weight	1.15kg

Physical Dimensions



Electrical

Power Input	AC 110V/240V	Control Mechanism	None
DC Current	2.5A	Controller	None
Power Consumption	30W	Data Wiring	None

Optical

Lens	None
Beam Angle	120°
Light Distribution	Symmetric direct illumination

Light Output

Color	Wavelength (nm)	Color Temp. (Typical)	Light Output (Lm)	Efficacy (Lm/W)
White	-	5600~6000K	1950	65
Warm White	-	2800K 3000K 3300K	1800	60