




**Waterproof RibbonStrip 5050**

FRB08-W180SMD-VF (White, 120°)  
FRB08-WW180SDM-VF (Warm White, 120°)

**Waterproof RibbonStrip 5050 Benefits:**


- Silica Rubber Tube Cover **Outdoor-Proof**
- **Ultra Brightness** / More than **120CM illumination distance**
- Ultimate **Flexibility** / **Low profile** / Convenient / Utility
- **Low Cost** Lighting Effects
- Extremely Low Operation Cost / Energy Efficient
- Super Long Life / Zero Maintenance
- **Constant Current Design**
- **Cutting Length** 3\*LED equal 50mm
- 120° viewing angle / **Saturated & Uniform Light** / No Cut-Off
- Application: All Indirect Lighting, Boarder-line, Signs, Glass Decoration, Cove Lighting, etc.



**Specification Features**

<b>Color Range</b>	White, Warm White, Red, Green, Blue, Amber
<b>Dimensions</b>	L3000mm x W13.5mm xH4.5mm
<b>Light Source</b>	180pcs 5050 Type 3-Chip SMD LED
<b>Housing</b>	None
<b>Operating Temperature</b>	-20°C to 50°C (-4°F to 122°F)
<b>Starting Temperature</b>	-10°C to 50°C (14°F to 122°F)
<b>IP Rating</b>	IP67
<b>LED source life</b>	50, 000 hours
<b>Design</b>	Flexible PCB / Silica Rubber Tube
<b>Connectors</b>	None
<b>Accessory</b>	Mounting Clip / End Cap
<b>Weight</b>	350g

**Physical Dimensions**



**Electrical**

<b>Power Input</b>	DC 12V
<b>DC Current</b>	60mA
<b>Power Consumption</b>	36W Max.

**Communication**

<b>Control Mechanism</b>	None
<b>Controller</b>	None
<b>Data wiring</b>	None

**Optical**

<b>Lens</b>	None
<b>Beam Angle</b>	120°
<b>Light Distribution</b>	Symmetric direct illumination

**Light Output**

Color	Wavelength (mm)	Color Temp. (Typical)	Luminous Intensity (mcd)	Power Consumption (W)
White	-	5700K	3600	33W
Warm White	-	3500K	3300	33W
Red	623-630		1400	36W
Green	522-525		3600	33W
Blue	462-468		560-700	33W
Amber	588-592		1400	36W